


# VIO-Verbinder, schwere, gegossene Serie feuerverzinkt


**V2 (101) kurzes T-Stück**



Reduzierte Varianten immer in Rohr A x B lesen!


Typ	Größe mm	EUR	kg
V02-27			0,19
V02-34			0,30
V02-42			0,46
V02-48			0,69
V02-60			0,96
V02-42/34			0,38
V02-48/34			0,44
V02-48/42			0,51
V02-60/48			0,58
V02-34/42			0,44
V02-42/48			0,44

**V9 (150) Innenverbinder**



Typ	Größe mm	EUR	kg
V09-34			0,30
V09-42			0,40
V09-48			0,50

**V3 (129) Geländer-T-Stück**



30°-60°


Typ	Größe mm	EUR	kg
V03-27			0,50
V03-34			0,50
V03-42			0,80
V03-48			0,90

**V10 (131) kurzer Fuß**



Typ	Größe mm	EUR	kg
V10-27			0,40
V10-34			0,55
V10-42			0,70
V10-48			0,95
V10-60			1,15

**V4 (104) langes T-Stück**




Typ	Größe mm	EUR	kg
V04-27			0,33
V04-34			0,49
V04-42			0,85
V04-48			1,10
V04-60			1,71

**V12 (132) langer Fuß**



Typ	Größe mm	EUR	kg
V12-27			0,50
V12-34			0,70
V12-42			1,00
V12-48			1,25
V12-60			1,75

**V5 (130) Geländer-Kniestück**




für Anschlüsse 30°-45°

Für Anschlüsse von Mittelgurten an Geländern!

Typ	Größe mm	EUR	kg
V05-34			1,05
V05-42			1,40
V05-48			1,70


**V13 (vormals V07/124) einstellbarer Bogen**



165°-120° bzw. 15°-60°

Typ	Größe mm	EUR	kg
V13-34			0,45
V13-42			0,65
V13-48			0,85

**V5T (127) Geländer-Kopfstück**



für Anschlüsse 30°-45°

Für Anschlüsse von Obergurten an Geländern!

Typ	Größe mm	EUR	kg
V05T-34			1,05
V05T-42			1,40
V05T-48			1,70

**V14 (144) Relingfuß, längs**



Typ	Größe mm	EUR	kg
V14-34			0,75
V14-42			1,45
V14-48			1,60


**V6 (125) Bogen 90°**



Reduzierte Variante


Typ	Größe mm	EUR	kg
V06-27			0,30
V06-34			0,40
V06-42			0,75
V06-48			0,90
V06-60			1,25
V06-48/42			1,25

**V15 (146) Stirnhalter**




Typ	Größe mm	EUR	kg
V15-34			0,75
V15-42			1,25
V15-48			1,55

**V8 (149) Kupplung**



Typ	Größe mm	EUR	kg
V08-27			0,30
V08-34			0,42
V08-42			0,60
V08-48			0,68
V08-60			1,05

**V16 (145) Relingfuß, quer**



Typ	Größe mm	EUR	kg
V16-34			0,85
V16-42			1,15
V16-48			1,66